


EN BHA product information sheet



BHA

Basic Hyper cooktop with integrated cooktop extractor – exhaust air

General product information:

Product:	Compact cooktop extractor system – a combined cooktop and extractor system
Product highlights:	Effective cooktop extractor including stainless steel grease filter, cooktop with four radiant cooking zones, simple central touch controls, Hyper cooking zone with up to 50% higher performance on the power setting
Model:	Exhaust air system with BORA Ecotube duct connection
Minimum installation dimensions:	Kitchen unit with a min. width of 80 cm
Safety and warning information:	See operating and installation instructions
Energy efficiency class:	

PISBHAEN-1000 1

BHA

Basic Hyper glass ceramic cooktop with integrated cooktop extractor – exhaust air

Technical data

Multiphase supply voltage	380-415 V 2N/3N
Supply voltage 1-phase	220-240 V
Frequency	50-60 Hz
Maximum power consumption	7000 W
3-phase fuse protection/power supply	3 × 16 A
2-phase fuse protection/power supply	2 × 16 A
1-phase fuse protection/power supply	1 × 32 A
Dimensions (width × depth × height)	760 × 515 × 196 mm
Weight (incl. accessories/packaging)	25 kg
Surface material	Glass ceramic
Cooktop extractor power levels	1, 2, P
Cooktop power levels	1-9, P
Size of front cooking zones	Ø 210 mm
Size of rear cooking zones	Ø 140 mm
Front cooking zone output	2300 W
Rear cooking zone output	1200 W
Output of front cooking zones on power setting	3000 W
Duct connection	BORA Ecotube

Product description

- Compact radiant cooktop
- Low volume
- Simple cleaning
- Stainless steel grease filter

Functions

Power setting, automatic after-run function, automatic heat-up function, heat retention function, cooking zone timer, short-time timer

Safety features

Child lock, residual heat indicator, safety shut-down, overheating protection

Scope of delivery

Hyper cooktop with integrated cooktop extractor – exhaust air BHA, air inlet nozzle GP4ED, stainless steel grease filter, horizontal exhaust air duct extension BLAVH1, operating and installation instructions, installation accessories

Accessories

Stainless steel grease filter BFF, air inlet nozzle for Basic/GP4 GP4ED, sealing tape UDB25, cooktop frame KFR760AB, side frame USL515/USL515AB, exhaust air duct extension BLAVH1, recirculation conversion set BUSU

Product and planning information

- The mains supply cable is to be provided on site
- Front power socket
- Flush installation or surface mounting possible
- Sufficient ventilation below the cooktop must be ensured
- Suitable for use with all BORA sockets

Installation options

Side view with horizontal exhaust air duct extension BLAVH1:

