



Technical data

Multiphase supply voltage	380 - 415 V 2N / 3N
Single-phase supply voltage	220 - 240 V
Frequency	50 - 60 Hz
Maximum power consumption	7360 W (4400 W / 3600 W)
Three-phase power supply/fuse protection	3 x 16 A
Two-phase power supply/fuse protection	2 x 16 A
Single-phase power supply/fuse protection	1 x 32 A (1 x 20 A / 1 x 16 A)
Dimensions (width x depth x height)	760 x 515 x 199 mm
Weight (incl. accessories/packaging)	23.9 kg

Cooktop

Surface material	Glass ceramic
Cooktop power levels	1 - 9, P
Front left cooking zone size	Ø 210 mm
Front left cooking zone output	2300 W
Front left cooking zone power setting output	3000 W
Rear left cooking zone size	Ø 175 mm
Rear left cooking zone output	1400 W
Rear left cooking zone power setting output	2100 W
Front right cooking zone size	210 x 210 mm
Front right cooking zone output	2100 W
Front right cooking zone power setting output	3000 W
Rear right cooking zone size	210 x 210 mm
Rear right cooking zone output	2100 W
Rear right cooking zone power setting output	3000 W

Cooktop extractor

Cooktop extractor power levels	1 - 3, P
Size of exhaust opening (W x H)	445 x 137 mm
Activated charcoal filter service life	150 hrs (1 year)

Product description

- Intuitive eControl control
- eSwap - easy filter change
- Effective odour removal
- Minimum volume
- Simple cleaning
- Optimum cooktop use
- Oversized surface induction cooking zones

Scope of delivery

- Cooktop with integrated cooktop extractor
- Air inlet nozzle
- Stainless steel grease filter
- Operating and installation instructions
- Installation clamps
- Sealing tape
- Height adjustment plate set
- Bag containing various small parts for assembly
- Odour filter (activated charcoal filter)
- Template for back panel cut-out
- Power supply cable (2 m)

Accessories

- GFES - eSwap odour filter
- GFESP - eSwap odour filter Plus
- KFR760AB - cooktop frame for width 760 mm
- RIED - Ring air inlet nozzle with hole to aid removal, black
- GAED - Gap air inlet nozzle with hole to aid removal, black
- ARED - Arc air inlet nozzle with hole to aid removal, black
- WAED - Wave air inlet nozzle with hole to aid removal, black
- PUEF - Pure stainless steel grease filter
- PULB - Pure air purification box
- PULBTA - Pure air purification box with telescopic pull-out
- USL515 - side frame
- USL515AB - side frame, All Black

Product- and planning instructions

- Front power socket
- The air purification box is fitted with a telescopic pull-out (extension to 80 mm) for connection to the back wall of the unit.
- The telescopic extension of the air purification box in extra-deep cooktop base cabinets can be extended by 105 mm with an additional telescopic extension PULBTA (available as accessory).
- Ensure sufficient ventilation of the area below the cooktop.
- Installation type: flush or surface-mounted
- The drawers and/or shelves in the floor unit must be removable for maintenance and cleaning purposes.
- Please note that induction-compatible cookware must be used on induction cooktops.
- The cooktop extractor system can be combined with all BORA sockets.